

# What lift is best for you?

Dur-A-Lift has been manufacturing truck mounted aerial lifts, for what is better known as a bucket truck, since 1969. We offer a wide variety of models for a variety of industries and applications. Here is a breakdown of what we have to offer.

**USE THIS GUIDE TO FIND THE RIGHT LIFT FOR YOU.**

# 1 - AERIAL LIFT SERIES

START BY NARROWING DOWN WHICH AERIAL LIFT SERIES BEST SUITS YOUR NEEDS.

**DPM2 & DLT2** - telescopic articulating, material handling or personnel aerial lift with 180° basket rotator, basket elevator and top mounted jib and winch

**DPM** - telescopic articulating, material handling or personnel aerial lift with 180° basket rotator and side mounted jib and winch

**DTAX** - telescopic articulating, aerial lift with 180° basket rotator

**DTA** - telescopic articulating aerial lift

**DHT** - heavy duty, telescopic aerial lift

**DT** - telescopic aerial lift

**DVS** - telescopic aerial lift for use with enclosed body (van series)

**DO** - articulating, overcenter aerial lift

**DFSL** - articulating, non-overcenter aerial lift

**DAT3** - telescopic articulating, non-overcenter forestry aerial lift

**Urban Forestry Unit** - telescopic articulating forestry truck with chipper box

**DCP** - telescopic articulating cable placer unit

	Telescopic	Articulating	Material Handling Option	Maximum Working Height	Maximum Side Reach	Insulated Option	Non-Insulated Option	2-person Basket Option	180° Basket Rotator	Basket Elevator Option	Basket Mount Style
TELESCOPIC ARTICULATED	<b>DLT2</b>	✓	✓	✓	67'	39' 2"	✓	✓	✓	✓	
	<b>DPM2</b>	✓	✓*	✓	39' - 59'	31' 6"	✓	✓	✓	✓	
	<b>DPM</b>	✓	✓*	✓	37' - 57'	31' 6"	✓	✓	✓	✓	
TELESCOPIC	<b>DTAX</b>	✓	✓		44' - 49'	30'	✓	✓		✓	
	<b>DTA</b>	✓	✓		40' - 45'	29' 6"	✓	✓			Side / End
VAN	<b>DHT</b>	✓			35' - 39'	26'	✓	✓		✓	
	<b>DT</b>	✓			34'	22' 3"	✓	✓			Side / End
ARTICULATED	<b>DVS</b>	✓			34'	21'		✓			Side / End
	<b>DO</b>		✓		37' - 41'	30' 4"	✓	✓			Side
FORESTRY	<b>DFSL</b>		✓		34' - 38'	19' 10"	✓	✓			Side
	<b>DAT3</b>	✓	✓		65' - 75'	48'	✓				End
CABLE PLACER	<b>UFU DATX-40/45</b>	✓	✓		45' - 50'	30'	✓	✓		✓	
	<b>DCP</b>	✓	✓		41'	26' 6"		✓			

\*Models DPM2-32 and DPM-32 are telescopic only

Material handling? Personnel?  
Telescopic? Articulated? Both?  
Insulated? Non-insulated?  
One person basket? Two person basket?

# 2 MODEL NUMBERS

HERE IS A BREAKDOWN OF ALL THE MODELS AVAILABLE WITH SPECIFICATIONS.

Model Number	Lift Type	Max Height	Max Side Reach	Stow Height	Insulated Option	Non-Insulated Option	2 Person Basket Available	Extension Travel	Main Boom Travel	Articulating Arm Travel	Lower Boom Travel	Upper Boom Travel	Lift Weight
<b>DLT2-60</b>	TA(M)*	67'	39' 2"	12'	✓	✓	✓	134"	-26° to 75°	0° to 91°	-	-	5950#
<b>DPM2-52</b>	TA(M)*	59'	31' 6"	11' 8"	✓	✓	✓	120"	-30° to 75°	0° to 75°	-	-	4400#
<b>DPM2-47</b>	TA(M)*	54'	31' 6"	10' 5"	✓	✓	✓	120"	-30° to 75°	0° to 75°	-	-	4300#
<b>DPM2-40</b>	TA(M)*	47'	31' 6"	10' 6"	✓	✓	✓	120"	-30° to 75°	0° to 75°	-	-	3900#
<b>DPM2-36</b>	TA(M)*	43'	27' 6"	10' 6"	✓	✓	✓	96"	-30° to 75°	0° to 75°	-	-	3700#
<b>DPM2-32</b>	T(M)*	39'	25' 4"	10' 8"	✓	✓	✓	120"	-15° to 80°	-	-	-	3300#
<b>DPM-52</b>	TA(M)*	57'	31' 6"	11' 8"	✓	✓	✓	120"	-30° to 75°	0° to 75°	-	-	4400#
<b>DPM-47</b>	TA(M)*	52'	31' 6"	10' 5"	✓	✓	✓	120"	-30° to 75°	0° to 75°	-	-	4300#
<b>DPM-40</b>	TA(M)*	45'	31' 6"	10' 6"	✓	✓	✓	120"	-30° to 75°	0° to 75°	-	-	3900#
<b>DPM-36</b>	TA(M)*	41'	27' 6"	10' 6"	✓	✓	✓	96"	-30° to 75°	0° to 75°	-	-	3700#
<b>DPM-32</b>	T(M)*	37'	25' 4"	10' 8"	✓	✓	✓	120"	-15° to 80°	-	-	-	3300#
<b>DTAX-44</b>	TA	49'	30'	10'	✓	✓		122.5"	-25° to 78°	0° to 82°	-	-	2800#
<b>DTAX-42</b>	TA	47'	28'	10'	✓	✓		110.5"	-25° to 78°	0° to 82°	-	-	2665#
<b>DTAX-39</b>	TA	44'	28'	10'	✓	✓		110.5"	-25° to 78°	-2° to 81°	-	-	2450#
<b>DTA-40</b>	TA	45'	29' 6"	10'	✓	✓		122.5"	-25° to 78°	0° to 82°	-	-	2750#
<b>DTA-38</b>	TA	43'	27' 6"	10'	✓	✓		110.5"	-25° to 78°	0° to 82°	-	-	2615#
<b>DTA-35</b>	TA	40'	27' 6"	10'	✓	✓		110.5"	-25° to 78°	-2° to 81°	-	-	2400#
<b>DHT-34</b>	T	39'	26'	9' 10"	✓	✓		128"	-22° to 82°	-	-	-	2700#
<b>DHT-32</b>	T	37'	24'	9' 10"	✓	✓		104"	-22° to 82°	-	-	-	2700#
<b>DHT-30</b>	T	35'	22'	9' 10"	✓	✓		104"	-22° to 82°	-	-	-	2600#
<b>DT-29</b>	T	34'	22' 3"	10' 6"	✓	✓		108"	-25° to 78°	-	-	-	1900#
<b>DVS-29</b>	T	34'	21'	10' 1"		✓		108"	-5° to 80°	-	-	-	2000#
<b>DO-36</b>	A	41'	30' 4"	9' 8"	✓	✓		-	-	-	0° to 100°	0° to 196°	2500#
<b>DO-32</b>	A	37'	26' 4"	9' 8"	✓	✓		-	-	-	0° to 100°	0° to 196°	2400#
<b>DFSL-36</b>	A	38'	19' 10"	10'	✓	✓		-	-	-	0° to 92°	0° to 133°	1950#
<b>DFSL-32</b>	A	34'	17' 10"	10'	✓	✓		-	-	-	0° to 92°	0° to 133°	1800#
<b>DAT3-70</b>	TA	75'	48'	12' 4"	✓			180"	-	-	0° to 95°	0° to 165°	8300#
<b>DAT3-60</b>	TA	65'	41' 3"	12' 4"	✓			144"	-	-	0° to 95°	0° to 165°	6800#
<b>UFU DTAX-45</b>	TA	50'	30'	11' 3"	✓	✓		122.5"	-25° to 78°	0° to 82°	-	-	2800#
<b>UFU DTAX-40</b>	TA	45'	28'	11' 2"	✓	✓		110.5"	-25° to 78°	-2° to 81°	-	-	2450#
<b>DCP-36</b>	TA	41'	26' 6"	10' 1"		✓		110.5"	-25° to 75°	-6° to 83°	-	-	2675#

T = Telescopic   A = Articulating   M = Material handling   \* Can be configured with or without material handling capabilities



# 3 INSULATED VS NON-INSULATED

The letter 'S' at the end of a model name signifies steel, meaning it is the non-insulated version of that lift. Anything without an 'S' is fiberglass. For example: DTAX is the insulated (fiberglass) version and DTAXS is the non-insulated (steel) version. Many of our lifts are available in both versions. The model names are as follows:

**DLT2 → DLT2S**

**DTAX → DTAXS**

**DT → DTS**

**DFSL → DSL\***

**DPM2 → DPM2S**

**DTA → DTAS**

**DVS (steel only)**

**DPM → DPMS**

**DHT → DHTS**

**DO → DOS**

\*The DFSL doesn't follow the standard non-insulated naming system. The F stands for fiberglass

# 4 BASKET STYLES/ TYPES OF CONTROLS

You may occasionally notice a series of letters at the end of a lift name, these signify either the basket style or the types of controls used to run the lift. For example: DPM-36 DU or DTAX-45 EP. Here are what the letters stand for and where you may see them used:

## TYPE OF CONTROLS

Here are the types of controls and what models they are available with. For example you may see DTAS-35 FP or DTAS-35 TS.

**DC** - Drive (battery) controls

**TS** - Two speed controls

**FP** - Full pressure controls

## BASKET STYLES

(APPLIES TO DPM, DPM2 and DLT2)

Our material handling aerial lifts are available with several basket styles. Since all of these lifts have full pressure (FP) controls the model name instead includes the basket style designation. For example: DPM-47 DU or DPM2-52 MH. Here is a breakdown of what the basket style abbreviations stand for:



**DP** - dual person, personnel

**DU** - dual configuration (dual person, personnel OR single person, material handling)

**MH** - single person, material handling

**SP\*** - single person, personnel

\*SP is available on DPM-36 and DPM-40 only

	DC	TS	FP
<b>DLT2 &amp; DLT2S</b>			✓
<b>DPM2 &amp; DPM2S</b>			✓
<b>DPM &amp; DPMS</b>			✓
<b>DTAX &amp; DTAXS</b>			✓
<b>DTA</b>			✓
<b>DTAS</b>	✓	✓	✓
<b>DHT &amp; DHTS</b>			✓
<b>DT</b>			✓
<b>DTS</b>	✓	✓	✓
<b>DVS</b>	✓	✓	
<b>DO &amp; DOS</b>			✓
<b>DFSL</b>	✓	✓	✓
<b>DAT3</b>			✓